

电站动力型谱表 ENGINE MODEL FOR GEN-SETS

发动机型号 Model	冷却方式 Cool-model	进气方式 Intake Mode	缸径/行程 Bore/Stroke mm	排量 Displacement L	常用功率 Prime-power kW	备用功率 Standby Power kW	外形尺寸 Dimension mm	重量 Weight kg	燃油/气消耗率 Fuel/Gas Consumption g/kW.h
50Hz									
F8L413F	风冷 Air-cooled	自然吸气 Naturally Aspirated	125/130	12.763	117/1500	129/1500	1081 × 1040 × 860	770	217
F12L413F	风冷 Air-cooled	自然吸气 Naturally Aspirated	125/130	19.144	176/1500	194/1500	1575 × 1038 × 956	1120	217
BF8L513	风冷 Air-cooled	增压 Turbocharged	125/130	12.763	147/1500	162/1500	1081 × 1144 × 1043	920	215
BF8L513C	风冷 Air-cooled	增压中冷 Turbocharged Inter-cooled	125/130	12.763	176/1500	194/1500	1081 × 1144 × 1043	1000	215
BF6M1015 -LA GA	水冷 Water-cooled	增压 Turbocharged	132/145	11.906	208/1500	231/1500	1043 × 932 × 1174	850	196
BF6M1015C -LA G1A	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	11.906	228/1500	250/1500	1043 × 932 × 1174	850	195
BF6M1015C -LA G2A	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	11.906	256/1500	285/1500	1043 × 932 × 1174	850	195
BF6M1015C -LA G3A	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	11.906	282/1500	314/1500	1043 × 932 × 1174	850	195
BF6M1015C -LA G4	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	11.906	310/1500	345/1500	1043 × 932 × 1174	850	195
BF6M1015CP -LA G	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	11.906	328/1500	365/1500	1043 × 932 × 1174	850	195
BF8M1015C -LA G1A	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	15.874	388/1500	418/1500	1151 × 955 × 1174	1060	196
BF8M1015C -LA G2	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	15.874	403/1500	448/1500	1151 × 955 × 1174	1060	196
BF8M1015CP -LA G1A	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	15.874	413/1500	459/1500	1151 × 955 × 1174	1060	196
BF8M1015CP -LA G2	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	15.874	448/1500	490/1500	1151 × 955 × 1174	1060	196
BF8M1015CP -LA G3	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	15.874	458/1500	509/1500	1151 × 955 × 1174	1060	196
BF8M1015CP -LA G4	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	15.874	/	530/1500	1151 × 955 × 1174	1060	196
BF8M1015CP -LA G5	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	15.874	/	560/1500	1151 × 955 × 1174	1060	196
HC12V132ZL -LA G1A	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	23.812	600/1500	670/1500	1763 × 920 × 1174	1600	197
HC12V132ZL -LA G2A	水冷 Water-cooled	增压中冷 Turbocharged Inter-cooled	132/145	23.812	666/1500	740/1500	1763 × 920 × 1174	1600	197

